

Datasheet

2U Intel single-CPU RI1204-AIXSG server

[Ver. 1.0]

Highlights at a glance:

- Incl. 1x Intel Xeon Silver 4309Y, can be equipped with a CPU (Intel Xeon Scalable 3rd Gen) up to 40 cores
- Incl. 16 GB RAM, upgradable to 1TB RAM, (8 DIMMs)
- 4x 2.5" (Hot-swap) up to 30.72 TB , SSDs: 30.72 TB
- Energy-efficient power supply red. NT
- Integrated IPMI (dedicated NIC)
- Optimally suited for use with desktop virtualization or GPU computing



Mainboards

Manufacturer	Supermicro	Supermicro	Supermicro
Mainboards	X12SPL-F	X12SPL-LN4F	X12SPi-TF
Chipset	Intel C621A	Intel C621A	Intel C621A
Socket	Intel LGA 4189	Intel LGA 4189	Intel LGA 4189
Processor	Intel Xeon Scalable 3rd Gen	Intel Xeon Scalable 3rd Gen	Intel Xeon Scalable 3rd Gen
Main Memory	8 DIMMs 1 TB DDR4 3200 RDIMM	8 DIMMs 1 TB DDR4 3200 RDIMM	8 DIMMs 1 TB DDR4 3200 RDIMM
LAN Onboard	2 x 1 GBit/s LAN (RJ-45)	4 x 1 GBit/s LAN (RJ-45)	2x 10 Gbit/s LAN (RJ-45)
LAN chipset	Intel i210	Intel i210	Intel X550
LAN Onboard (dedicated IPMI)	1x RJ45 Dedicated IPMI LAN port	1x RJ45 Dedicated IPMI LAN port	1x RJ45 Dedicated IPMI LAN port
Onboard graphic	1x VGA ASPEED AST2600 BMC	1x VGA ASPEED AST2600 BMC	1x VGA ASPEED AST2600 BMC
Additional card (optional)	PNY NVIDIA Quadro T1000 (4GB)	PNY NVIDIA Quadro T1000 (4GB)	PNY NVIDIA Quadro T1000 (4GB)
Onboard Input/Output	USB (no PS2 ports!) 1x TPM Header 1x COM Port (header)	USB (no PS2 ports!) 1x TPM Header 1x COM Port (header)	USB (no PS2 ports!) 1x TPM Header 1x COM port (rear)
USB ports	4x USB (rear) 1x USB on board (type A)	4x USB (rear) 1x USB on board (type A)	4x USB (rear) 1x USB on board (type A)

Extension-slots for additional cards

PCI slots (mainboard)	3x PCIe 3.0 x8 2x PCIe 4.0 x16 2x PCIe 4.0 x8	3x PCIe 3.0 x8 2x PCIe 4.0 x16 2x PCIe 4.0 x8	3x PCIe 4.0 x16 2x PCIe 4.0 x8
Available slots in the chassis	2x	2x	2x

Onboard ports

SATA-3 (6 Gb/s)	12x SATA-3 (6 Gbit/s) Intel C621A RAID 0, 1, 10, 5, Software-Raid	12x SATA-3 (6 Gbit/s) Intel C621A RAID 0, 1, 10, 5, Software-Raid	10x SATA-3 (6 Gbit/s) Intel C621A RAID 0, 1, 10, 5, Software-Raid
Port distribution	8x Intel PCH 0x Intel SCU 2x SuperDOM support	8x Intel PCH 0x Intel SCU 2x SuperDOM support	8x Intel PCH 0x Intel SCU 2x SuperDOM support
M.2	1 x M.2 PCIe 3.0 x4, SATA	1 x M.2 PCIe 3.0 x4	1 x M.2 PCIe 3.0 x4, SATA
M.2 form factor	2280, 22110	2280, 22110	2280, 22110
NVMe	0x NVMe onboard	0x NVMe onboard	2x NVMe onboard

Drives / storage capacity

Drive slots (total)	4x 2.5" (Hot-swap)
SAS / SATA slots	4x SAS / SATA
Backplane	SATA / SAS-3 (12 Gb/s)
Max. capacity HDD (SATA)	30.72 TB
Max. capacity SSD (SATA)	30.72 TB

Server management

Management software	Supermicro SuperDoctor 5
Remote management	Integrated IPMI (dedicated NIC)
Features	Managementsoftware IPMI View IPMI with KVM Over LAN Serial Over LAN (SOL) Virtual Media Over LAN (Virtual USB Floppy/CD and Drive Redirection) LAN Alert-SNMP Trap Event Log OS Independent Hardware Health Monitor Remote Power Control Support RMCP & RMCP + Protocols Fan Speed Control Dedicated 3. network interface card
IPMI-sensors	CPU-temperature (OK / warning) system-temperature (Celsius degree) Electronic voltage (volt) Cooler speed (RPM) Additional model-dependent sensors (www.thomas-krenn.com/ipmi-sensoren)

Chassis

Unit	2U
Dimensions	88 mm (H), 438 mm (W), 450 mm (D),
drives (in scope of delivery)	not contained, optional available
Drives (optional)	External USB-drives
Fan (center)	4 60x60x32mm Hot-swap (,)
Silent blowerkit option	no
Front USB ports	2

Rack Assembly

Assembly rails	optionally available
----------------	----------------------

environment-requirements

Recommended ambient temperature	20 - 22 degree
Recommended humidity	max. 40%
Recommended deployment location	To ensure the optimal cooling of the system, we recommend running the server in an air conditioned server room and as part of a rack installation. The server is not ideal for use in an office environment due to its high noise levels.