



Features & Benefits

- Optimized interval between two HDD carriers to deliver best cooling performance
- Maximum venting area on front bezel and dedicated venting holes for add-on cards and CPU
- Utilizing 120mm PSU fan to exhaust heated air and for quiet operation
- Built-in 4-port 6Gb/s backplane for SAS and SATA drives
- Padlock loop, Kensington slot and intrusion switch support
- Front bezel lock preventing unauthorized access

Specification

M/B Form Factor	• Mini-ITX (6.7"x 6.7")
Dimension (D x W x H)	• 310 x 200 x 270(mm),
	• 12.2" x 7.87" x10.63"
Drive Bay	• 4 x 3.5" Hot-swap
	• 2 x 2.5"
PSU Form Factor	• PS/2 Single
Indicator	• 1 x Power Status, 1 x HDD Activity, 1 x Warning LED
Front Control	• Power On/Off, System Reset, 2x USB2.0
System Security	• Padlock Loop, Kensington slot, Intrusion switch
Cooling Fan	• Front: 1x120mm
Slot Opening	• 1x Low Profile
HDD Backplane	• 6Gb/s SAS & SATA
Metal Thickness	• 0.7mm
Net Weight	• 5.2kg
Gross Weight	• 7kg
Front Bezel	• Option
Cubic Feet	• 1.85
Container Loading	• 20':564, 40':1134, 40'HQ:1284 (Single Carton)

Compact size with outstanding performance and mass storage









