

FWA-1112VC



System	CPU	Intel® Atom® C3558 (-4CA1S) Intel® Atom® C3758 (-8CA1S)
	QAT Technology	Yes
	Memory	up to 32GB RAM (1x 32GB)
	Storage	1x M.2 2280 SATA SSD
	Console	1x RJ45 port
	Display	NA
	Ethernet	4x 1G RJ45 2x 10G SFP+
	Front I/O Panel	2x USB 3.0 1x Power Button 4x LAN 100/1000 2x LAN SFP+ 1x Console RJ45
	Rear I/O Panel	1x 12V DC Power in 2x Sim Socket
Environment	Operating Temperature	0 – 70 °C with 0.7m/s air flow (0 – 60 °C C3758) -20 – 70 °C with 0.7m/s air flow by SKU option
	Humidity	10 ~ 95% @ 40 °C, non-condensing
	Vibration (5 ~ 500 Hz)	1 Grms
	Shock	10 G (with 11 ms duration, half sine wave)
	IP	IP40
Cooling	Chassis Fan	-
	Air Filter	-
Power Supply	Power Supply	12V DC 3A, 36W
Physical Characteristics	Dimension (HxBxT)	44 x 220 x 160 mm
OS	Windows	-
	Linux	Linux 64-bit
Optional		LTE/5G WiFi/BT Rackmount Kit Wallmount Kit PoE
Available		2029