Datenblatt

OPNsense Desktop Appliance S



Highlights auf einem Blick:

- Industrielles Design
- Qualitativ hochwertige Industriekomponenten
- Für den 24/7 Dauerbetrieb geeignet
- OPNsense Community Edition vorinstalliert
- Geeignet mit den OPNsense Grundfunktionen für kleine Büros bis 30 MA
- Auch zur Vernetzung von kleinen Remote-Standorten und Zweigstellen geeignet
- Front-IO Rackmount Kit inklusive
- Einsetzbar bei einer Umgebungstemperatur von 0 - 40 °C

	System
CPU	Intel® Atom® C3558 (-4CA1S) Intel® Atom® C3758 (-8CA1S)
QAT Technology	Yes
Memory	up to 64GB RAM (2x 32GB)
Storage	1x M.2 2280 SATA SSD
Console	1x RJ45 port
Display	NA
Ethernet	4x 1G RJ45 (-8CA1S) / 6x 1G RJ45 (-8CA1S) 2x 1G SFP
Front I/O Panel	-
Rear I/O Panel	2x USB 3.0 1x Power Button 4x LAN 100/1000 / 6x LAN 100/1000 2x LAN SFP 1x Console RJ45 1x 12V DC Power in 2x Sim Socket

THOMAS KRENN®
IT's people business

	Environment
Operating Temperature	0 – 40 °C with 0.7m/s air flow
Humidity	10 ~ 95% @ 40 °C, non-condensing
Vibration (5 ~ 500 Hz)	1 Grms
Shock	10 G (with 11 ms duration, half sine wave)
IP	-
	Cooling
Chassis Fan	1 / 2
Air Filter	-
	Power Supply
Power Supply	12V DC 5A, 60W
	Physical Characteristics
Dimension (HxBxT)	44 x 250 x 193 mm
	OS
Windows	-
Linux	Linux 64-bit
	Optional
	LTE WiFi/BT Rackmount Kit Wallmount Kit PoE
	Available
	2029

THOMAS KRENN®
IT's people business