

# WD VelociRaptor™ SATA Hard Drives

Killer Speed  
Rock-solid Reliability  
5-year Limited Warranty



## Interface

SATA 3 Gb/s

## Width/Height

2.5-inch/0.6-inch

## Rotational Speed

10,000 RPM

## Capacities

150 GB  
300 GB

## Model Numbers

WD1500BLFS  
WD3000BLFS

*Note:* Not all products may be available in all regions of the world.

Engineered for maximum speed! WD VelociRaptor, the newest member of our unique class of 10,000 RPM SATA hard drives, combines a SATA 3 Gb/s interface and 16 MB cache, to deliver performance that's up to 35% faster than its speedy older brother, the WD Raptor®.

### Product Benefits

**Killer speed** – Built on the performance bloodlines of WD Raptor, these 10,000 RPM drives, with SATA 3 Gb/s interface and 16 MB cache, deliver mind-bending performance. Not only are they 35% faster than the previous generation of WD Raptor drives, but they also beat out all other competitors in the field.

**Rock-solid reliability** – Designed and manufactured to mission-critical enterprise-class standards to provide enterprise reliability in high duty cycle environments. With 1.4 million hours MTBF, these drives have the highest available reliability rating on a high-capacity SATA drive.

**Double the capacity** – State-of-the-art technology packs twice the capacity per disk compared to its older brother WD Raptor, resulting in 300 GB of high-performance storage space in this enterprise-class 2.5-inch drive.

**Small form factor** – This ultra fast 2.5-inch hard drive is engineered to fit into blade servers and other enterprise storage configurations. (Not designed for use in laptop or notebook computers)

**Ultra-cool operation** – WD VelociRaptor consumes 35% less power than the previous generation of WD Raptor.

**Rotary Acceleration Feed Forward (RAFF™)** – Optimizes operation and performance when the drives are used in vibration-prone, multi-drive chassis.

**NoTouch™ ramp load technology** – The recording head never touches the disk media ensuring significantly less wear to the recording head and media as well as better drive protection in transit.

### The WD Promise



WD understands the importance of the information you save to your hard drive and we are committed to protecting that data with exceptionally reliable products, advanced data protection technology, and superior customer support. No one does more to safeguard your data than WD.

# WD VelociRaptor

## SATA Hard Drives

### Physical Specifications<sup>1</sup>

	150 GB	300 GB
Formatted capacity	150,039 MB	300,069 MB
User sectors per drive	293,046,768	586,072,368
WD model number	WD1500BLFS	WD3000BLFS
SATA latching connector	Yes	Yes
Bytes per sector (STD)	512	512
Form factor	2.5-inch	2.5-inch
Interface	SATA 3 Gb/s	SATA 3 Gb/s
RoHS compliant <sup>2</sup>	Yes	Yes



### Performance Specifications<sup>1</sup>

Average latency	3 ms
Buffer	16 MB
Cache	
Read	Adaptive
Write	Yes
Data transfer rate (maximum)	
Buffer to host	3 Gb/s
Host to/from drive	126 MB/s sustained
Drive ready time	7.0 sec (average), 10 sec (maximum)
Error rate (non-recoverable)	<1 in 10 <sup>15</sup> bits read
LBA support	Yes
Rotational speed	10,000 RPM
Seek time	
Read	4.2 ms (average)
Write	4.7 ms (average)
Track-to-track seek time	0.7 (maximum)
Load/unload cycles	50,000 minimum
Limited warranty <sup>3</sup>	5-year



#### For service and literature:

[support.wdc.com](http://support.wdc.com)  
[www.westerndigital.com](http://www.westerndigital.com)

800.ASK.4WDC North America  
 800.832.4778 Latin America (Spanish)  
 +800.6008.6008 Asia Pacific  
 +800.ASK.4WDEU Europe (toll free where available)  
 +31.88.0062100 Europe, Middle East, Africa

<sup>1</sup>As used for storage capacity, one megabyte (MB) = one million bytes, one gigabyte (GB) = one billion bytes, and one terabyte (TB) = one trillion bytes. Total accessible capacity varies depending on operating environment. As used for buffer or cache, one megabyte (MB) = 1,048,576 bytes. As used for transfer rate or interface, megabyte per second (MB/s) = one million bytes per second, megabit per second (Mb/s) = one million bits per second, and gigabit per second (Gb/s) = one billion bits per second. Effective maximum SATA 3 Gb/s or 1.5 Gb/s transfer rate calculated according to the Serial ATA specification published by the SATA-IO organization as of the date of this specification sheet. Visit [www.sata-io.org](http://www.sata-io.org) for details.

<sup>2</sup>WD products manufactured and sold worldwide after August 1, 2005, meet or exceed Restriction of Hazardous Substances (RoHS) compliance requirements as mandated by the European Union for electrical and electronic products. The RoHS Directive 2002/95/EC of the European Parliament, which is effective in the EU beginning July 1, 2006, aims to protect human health and the environment by restricting the use of certain hazardous substances in new equipment, and consists of restrictions on lead, mercury, cadmium, and other substances.

<sup>3</sup>Standard five-year limited warranty, unless otherwise required by law. For extended warranty information, visit our Web site at [support.wdc.com](http://support.wdc.com).

Western Digital, WD, WD Raptor, and the WD logo are registered trademarks in the U.S. and other countries; and WD VelociRaptor, NoTouch, RAFF, and FIT Lab are trademarks of Western Digital Technologies, Inc. Other marks may be mentioned herein that belong to other companies. Product specifications subject to change without notice.

© 2008 Western Digital Technologies, Inc.  
 All rights reserved.

Western Digital  
 20511 Lake Forest Drive  
 Lake Forest, California 92630 U.S.A.

2879-701282-A01 Dec 2008