

PRODUCT BRIEF

Intel® Solid-State Drive DC S3500 Series

Non-Volatile Memory Storage Solutions from Intel

Consistently Amazing

Premier Performance, Protection, and Optimization for the Data Center

The Intel® Solid-State Drive DC S3500 Series offers the next generation of data center SSDs combining fast consistent read performance with strong data protection, and leading edge 20nm flash technology.

Fast and Consistent Performance

Deliver data at a rapid pace, with consistently low latencies and tight IOPS distribution.

The Intel® Solid-State Drive DC S3500 Series delivers superior Quality of Service for applications such as video streaming/conferencing, virtual client support, and big data analytics. All of these applications benefit from 50µs typical latency with max read latencies² of 500µs for 99.9% of the time and 4KB random read performance of up to 75,000 input/output operations per second (IOPS)¹. Performance delivered with low active read power (less than 1.3 watts¹) means this Intel SSD helps improve data center efficiency with reduced energy costs—making it an excellent value for data center storage application upgrades!

Stress-free Data Protection

Protect your data center applications with multiple security checkpoints providing protection against data loss and corruption. The Intel® SSD DC S3500 Series combines the following features to provide an SSD you can count on.

Full End-to-End Data Protection. Protects your data from the time it enters the drive to the time it leaves. The Intel® SSD DC S3500 Series uses an advance error correction scheme that ensures data integrity by protecting against possible data corruption in the NAND, SRAM, and DRAM memory. The Intel® SSD DC S3500 Series also protects the data in transit through several techniques such as parity checks, Cyclic Redundancy Checks (CRC) and LBA tag validation. Once an error is detected, an immediate attempt will be made to correct it, and any uncorrectable error will be reported to the host. To further improve data assurance, the Intel® SSD DC S3500 Series provides data redundancy technology to minimize potential data loss.

Enhanced Power-Loss Data Protection. Reduces potential data loss by detecting and protecting data from an unexpected system power loss. The drive saves all cached data in the process of being written prior to shutting down, thereby reducing potential data loss.

Optimized for Efficiency

Reduce the strain on tight IT budgets with leading Intel technologies. By combining the latest 20nm Multi-Level Cell (MLC) NAND flash memory technology with Intel's latest SSD controller technology, the Intel® SSD DC S3500 Series delivers fast and consistent performance, reduced power consumption and stress-free data protection. Optimize your dollars per IOP, energy costs, and floor space in your data center with the amazingly efficient Intel® SSD DC S3500 Series.

Solid-State Computing Starts with Intel Inside®. For more information, visit www.intel.com/go/ssd



Product Spotlight

- *Fast and Consistent Performance*
- *Full End to End Data Protection*
- *Enhanced Power-Loss Data Protection*
- *Latest 20nm MLC NAND Flash Memory Technology*
- *Intel based controller technology*

PRODUCT BRIEF: Intel® Solid-State Drive DC S3500 Series

Technical Specifications ¹																
Model Name	Intel® Solid-State Drive DC S3500 Series															
Capacity	2.5": 80GB, 120GB, 160GB, 240GB, 300GB, 480GB, 600GB and 800GB 1.8": 80GB, 240GB, 400GB and 800GB															
NAND Flash Memory	20nm Intel® NAND Flash Memory Multi-Level Cell Compute-Quality Components															
Bandwidth ²	Sustained Sequential Reads/Writes															
	<table border="0"> <tr> <td>2.5" 80GB: up to 340 / 100 MB/s</td> <td>1.8" 80GB: up to 340 / 100 MB/s</td> </tr> <tr> <td>120GB: up to 445 / 135 MB/s</td> <td>240GB: up to 500 / 260 MB/s</td> </tr> <tr> <td>160GB: up to 475 / 175 MB/s</td> <td>400GB: up to 500 / 380 MB/s</td> </tr> <tr> <td>240GB: up to 500 / 260 MB/s</td> <td>800GB: up to 500 / 450 MB/s</td> </tr> <tr> <td>300GB: up to 500 / 315 MB/s</td> <td></td> </tr> <tr> <td>480GB: up to 500 / 410 MB/s</td> <td></td> </tr> <tr> <td>600GB: up to 500 / 410MB/s</td> <td></td> </tr> <tr> <td>800GB: up to 500 / 450 MB/s</td> <td></td> </tr> </table>	2.5" 80GB: up to 340 / 100 MB/s	1.8" 80GB: up to 340 / 100 MB/s	120GB: up to 445 / 135 MB/s	240GB: up to 500 / 260 MB/s	160GB: up to 475 / 175 MB/s	400GB: up to 500 / 380 MB/s	240GB: up to 500 / 260 MB/s	800GB: up to 500 / 450 MB/s	300GB: up to 500 / 315 MB/s		480GB: up to 500 / 410 MB/s		600GB: up to 500 / 410MB/s		800GB: up to 500 / 450 MB/s
2.5" 80GB: up to 340 / 100 MB/s	1.8" 80GB: up to 340 / 100 MB/s															
120GB: up to 445 / 135 MB/s	240GB: up to 500 / 260 MB/s															
160GB: up to 475 / 175 MB/s	400GB: up to 500 / 380 MB/s															
240GB: up to 500 / 260 MB/s	800GB: up to 500 / 450 MB/s															
300GB: up to 500 / 315 MB/s																
480GB: up to 500 / 410 MB/s																
600GB: up to 500 / 410MB/s																
800GB: up to 500 / 450 MB/s																
Read / Write Latency	50 µs / 65 µs															
Random I/O Operations per Second	4KB Reads / Writes															
	<table border="0"> <tr> <td>2.5" 80GB: up to 70,000 IOPS / 7,000 IOPS</td> <td>1.8" 80GB: up to 70,000 IOPS / 7,000 IOPS</td> </tr> <tr> <td>120GB: up to 75,000 IOPS / 4,600 IOPS</td> <td>240GB: up to 75,000 IOPS / 7,500 IOPS</td> </tr> <tr> <td>160GB: up to 75,000 IOPS / 7,500 IOPS</td> <td>400GB: up to 75,000 IOPS / 11,000 IOPS</td> </tr> <tr> <td>240GB: up to 75,000 IOPS / 7,500 IOPS</td> <td>800GB: up to 75,000 IOPS / 15,500 IOPS</td> </tr> <tr> <td>300GB: up to 75,000 IOPS / 9,000 IOPS</td> <td></td> </tr> <tr> <td>480GB: up to 75,000 IOPS / 11,000 IOPS</td> <td></td> </tr> <tr> <td>600GB: up to 75,000 IOPS / 11,000 IOPS</td> <td></td> </tr> <tr> <td>800GB: up to 75,000 IOPS / 11,500 IOPS</td> <td></td> </tr> </table>	2.5" 80GB: up to 70,000 IOPS / 7,000 IOPS	1.8" 80GB: up to 70,000 IOPS / 7,000 IOPS	120GB: up to 75,000 IOPS / 4,600 IOPS	240GB: up to 75,000 IOPS / 7,500 IOPS	160GB: up to 75,000 IOPS / 7,500 IOPS	400GB: up to 75,000 IOPS / 11,000 IOPS	240GB: up to 75,000 IOPS / 7,500 IOPS	800GB: up to 75,000 IOPS / 15,500 IOPS	300GB: up to 75,000 IOPS / 9,000 IOPS		480GB: up to 75,000 IOPS / 11,000 IOPS		600GB: up to 75,000 IOPS / 11,000 IOPS		800GB: up to 75,000 IOPS / 11,500 IOPS
2.5" 80GB: up to 70,000 IOPS / 7,000 IOPS	1.8" 80GB: up to 70,000 IOPS / 7,000 IOPS															
120GB: up to 75,000 IOPS / 4,600 IOPS	240GB: up to 75,000 IOPS / 7,500 IOPS															
160GB: up to 75,000 IOPS / 7,500 IOPS	400GB: up to 75,000 IOPS / 11,000 IOPS															
240GB: up to 75,000 IOPS / 7,500 IOPS	800GB: up to 75,000 IOPS / 15,500 IOPS															
300GB: up to 75,000 IOPS / 9,000 IOPS																
480GB: up to 75,000 IOPS / 11,000 IOPS																
600GB: up to 75,000 IOPS / 11,000 IOPS																
800GB: up to 75,000 IOPS / 11,500 IOPS																
Interface	SATA 6Gb/s, compatible with SATA 3Gb/s and 1.5Gb/s.															
Form Factor, Height and Weight	2.5 inch and 1.8" Industry Standard Form Factor															
	Height: 2.5" 7.0 mm thick; 1.8" 5 mm thick Weight: 2.5" 80GB - 240GB: 70 grams ± 2 grams 2.5" 300GB - 800GB: 72 grams ± 2 grams; 1.8" 80GB: 35 grams ± 2 grams 1.8" 240-800GB: 37 grams ± 2 grams															
Life Expectancy	2 million hours Mean Time Between Failures (MTBF)															
Lifetime Endurance ³	Up to 450TB Written															
Usage ⁴	24/7 operation															
Power Consumption	Read: 1.3 W Typical Write: 5.0 W Typical Idle: 650 mW Typical															
Operating Temperature	0° C to 70° C															
RoHS Compliance	Meets the requirements of European Union (EU) RoHS Compliance Directives															
Product Health Monitoring	Self-Monitoring, Analysis and Reporting Technology (S.M.A.R.T.) commands															
Product Ordering Information	To order, visit intel.com/go/ssd															

¹ Based on the Intel® SSD DC S3500 Series Product Specification.

² Device measured using Iometer with 4K Random Writes QD=32 across 100% span of the drive. Latency measured using write transfer size of 4KB (4,096 bytes) and queue depth set to 1.

³ Based on JESD218 standard with JESD219 workload

⁴ Based on JESDEC SSD standard Jc64.8

INFORMATION IN THIS DOCUMENT IS PROVIDED IN CONNECTION WITH INTEL PRODUCTS. NO LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE, TO ANY INTELLECTUAL PROPERTY RIGHTS IS GRANTED BY THIS DOCUMENT. EXCEPT AS PROVIDED IN INTEL'S TERMS AND CONDITIONS OF SALE FOR SUCH PRODUCTS, INTEL ASSUMES NO LIABILITY WHATSOEVER, AND INTEL DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY, RELATING TO SALE AND/OR USE OF INTEL PRODUCTS INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, MERCHANTABILITY, OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT. UNLESS OTHERWISE AGREED IN WRITING BY INTEL, THE INTEL PRODUCTS ARE NOT DESIGNED NOR INTENDED FOR ANY APPLICATION IN WHICH THE FAILURE OF THE INTEL PRODUCT COULD CREATE A SITUATION WHERE PERSONAL INJURY OR DEATH MAY OCCUR.

Intel may make changes to specifications and product descriptions at any time, without notice. Designers must not rely on the absence or characteristics of any features or instructions marked "reserved" or "undefined." Intel reserves these for future definition and shall have no responsibility whatsoever for conflicts or incompatibilities arising from future changes to them. The information here is subject to change without notice. Do not finalize a design with this information.

Performance tests and ratings are measured using specific computer systems and/or components and reflect the approximate performance of Intel products as measured by those tests. Any difference in system hardware or software design or configuration may affect actual performance. Buyers should consult other sources of information to evaluate the performance of systems or components they are considering purchasing. For more information on performance tests and on the performance of Intel products, go to: http://www.intel.com/performance/resources/benchmark_limitations.htm.

The products described in this document may contain design defects or errors known as errata which may cause the product to deviate from published specifications. Current characterized errata are available on request. Contact your local Intel sales office or your distributor to obtain the latest specifications and before placing your product order. Copies of documents which have an order number and are referenced in this document, or other Intel literature, may be obtained by calling 1-800-548-4725, or by visiting Intel's Web site at www.intel.com.

*Other names and brands may be claimed as the property of others.

Copyright © 2013 Intel Corporation. All rights reserved. Intel, the Intel logo, and Intel Inside are trademarks of Intel Corporation in the U.S. and other countries.

Printed in USA 9/2013/PsA/PDF

Please Recycle

328964-001US