

Datasheet

Rittal 42U Server Cabinet

[Ver. 1.0]

Highlights at a glance:

- Perforated transparent door in a honeycomb pattern or with 3 mm tempered safety glass (ESG)
- Universal rails for server, network and electronic applications
- Depth variable rails
- Markings for unit height
- Multi-piece roof panel for side cable entry on the entire length of the cabinet
- Comfort handle incl. security lock
- Flexible and tool-less anchoring of the rails via quick release clamps



Dimensions

Unit	42U
Height	2000 mm (78.75")
Width	800 mm (W)
Depth	1200 mm (D)
Weight	98.6 kg

specifications

capacity	15000 N (1.53 T)
----------	------------------

material / surface

Base frame	Cabinet frame: primed, Interior: primed
Color	frame and flat parts: RAL 7035, interior design: RAL 9005

Scope of supply / Delivery condition

Scope of delivery	1x ventilated steel door (ca. 85% perforated area sheet metal), (180°), with comfort handle for semi-cylinder and security lock 3524 E 1x ventilated steel door (ca. 85% perforated area sheet metal), (180°), divided vertically, with comfort handle for semi-cylinder and security lock 3524 E 2x 482.6 mm (19") front and back attachment depth variable unit with quick fasteners 1x multi-piece, removable Roof Plate with side cable entry at the base and a covered exhaust for the fan module 4x Spacers for passive ventilation (not mounted) 1 Grounding Set with a central ground point (not mounted) 50x Torx (star) screws M5, Cage Nuts M5, conductive (not mounted)
Side panels	Not included, optionally available

optional accessories

Multiple socket outlets	<ul style="list-style-type: none"> • 6fach Steckleiste m. Überspannungsschutz/Filter • Power strip 8fold IP 19
-------------------------	--