

Datasheet

2U Intel Dual-CPU RI2208-AIXSN+ Server

[Ver. 3.0]

Highlights at a glance:

- Incl. 1x Intel Xeon Silver 4410Y, expandable to up to 2x CPUs (Intel Xeon Scalable 4th Gen or 5th Gen) up to 60 cores
- Incl. 32 GB RAM, upgradeable up to 384GB RAM, (16 DIMMs)
- 8x 3.5" / 2.5" drives (hot-swap) – SATA/SAS/NVMe depending on backplane selection
- 2 x 2.5"(Rear, hot-swap), optional 2 2.5" (rear of chassis, hot-swap)
- Expandable with 6 LP/ HL/ FL add-on card(s), 6x PCIe 5.0 x16
- 10GBase-T dual-port on board LAN (optional)
- Energy-efficient power supply 80 PLUS Titanium (>96%) red. NT
- Integrated IPMI (dedicated NIC)
- Toolless design (drives, power supplies, fans, backplane)



Mainboards

Manufacturer	Gigabyte
Mainboards	MS73-HB0
Chipset	Intel C741
Socket	Intel LGA 4677
Processor	Intel Xeon Scalable 4th/5th Gen (Sapphire/Emerald Rapids)

Main Memory	16 DIMMs 384 GiB DDR5 4800/5600 RDIMM
LAN Onboard	2 x 1 GBit/s LAN (RJ-45) 2x 10 Gbit/s LAN (RJ-45)
LAN chipset	Intel I210-AT, Intel X710-AT2
Onboard graphic	1x VGA ASPEED AST2600 BMC 2 GiB
Onboard graphics maximum resolution	1920x1200@60Hz
Additional card (optional)	PNY NVIDIA RTX A1000 (8GB)
USB ports	2x USB (rear) 3.2 Gen1 3.2 Gen1 2x USB on board (type A) 3.2 Gen1

Extension-slots for additional cards

PCI slots (mainboard)	6x PCIe 5.0 x16
Available slots in the chassis	6x Low profile/Half Length/Full Length

Onboard ports

SATA-3 (6 Gb/s)	14x SATA-3 (6 Gbit/s)
M.2	2 x M.2 PCIe 3.0 x4
M.2 form factor	2280, 22110

Drives / storage capacity

Drive slots (total)	8x 3.5" / 2.5" (Hot-swap) 2x 2.5" (Rear, hot-swap) 22.5" (rear of chassis, hot-swap)
Backplane	SATA / SAS-3 / NVMe (12 Gb/s)
Max. capacity HDD (SAS)	64 TB
Max. capacity HDD (SATA)	15.36 TB
Max. capacity SSD (SATA)	15.36 TB
Max. capacity SSD (U.2 NVMe)	122.4 TB

Server management

Management software	GIGABYTE Management Console
Remote management	Integrated IPMI (dedicated NIC)

Chassis

Unit	2U
Dimensions	88 mm (H), 430 mm (W), 680 mm (D),
Drives (optional)	External USB-drives
Fan (center)	3 80x80x38mm Hot-swap (8600rpm, 62.5dBA)
Silent blowerkit option	no
Front USB ports	1

Power supply

Power supply unit	2x 800 Watt redundantes Hot Swap Netzteil (80 plus Titanium)
energy efficiency	96%

Rack Assembly

Assembly rails	contained in the scope of supply
----------------	----------------------------------

environment-requirements

Recommended ambient temperature	0 - 40 °C
Recommended humidity	0 - 95% (non-condensing)
Recommended deployment location	To ensure the optimal cooling of the system, we recommend running the server in an air conditioned server room and as part of a rack installation. The server is not ideal for use in an office environment due to its high noise levels.