


# Datasheet

## 2U Intel dual-CPU RI2224-TKXSN server

[Ver. 2.0]

### Highlights at a glance:

- Incl. 1x Intel Xeon Silver 4410Y, can be expanded to up to 2x CPUs (12 - 12 cores)
- Incl. 32 GB RAM, upgradeable up to 384GB RAM, (32 DIMMs)
- 24 drives (Hot-swap), capacities up to 367.2 TB (NVMe)
- Optional additional drives: 2x 2.5"
- 2x 10 Gbit/s LAN (RJ-45)
- Expandable with 3 add-on card(s)
- Energy-efficient power supply 80 PLUS Titanium (>96%) red. NT
- Integrated IPMI (dedicated NIC)



### Mainboards

Manufacturer	Thomas-Krenn.AG
Mainboards	TKXS-DP-I4
Socket	Intel LGA 4677
Processor	Intel Xeon Scalable 4th/5th Gen (Sapphire/Emerald Rapids)
Main Memory	32 DIMMs 384 GiB DDR5 4800 RDIMM
LAN Onboard (dedicated IPMI)	1
USB ports	1x USB on board (type A)

## Extension-slots for additional cards

Available slots in the chassis	3x
--------------------------------	----

## Onboard ports

M.2	2 x M.2 PCIe 3.0 x4
M.2 form factor	2280

## Drives / storage capacity

Drive slots (total)	24 (Hot-swap) 2x 2.5"
NVMe slots	16x  NVMe
NVMe / SAS / SATA hybrid slots	8x NVMe / SAS / SATA (hybrid)
Backplane	SATA / SAS-3 / NVMe (12 Gb/s)
Max. capacity HDD (SATA)	15.36 TB
Max. capacity SSD (SATA)	15.36 TB
Max. capacity SSD (U.2 NVMe)	367.2 TB

## Server management

Remote management	Integrated IPMI (dedicated NIC)
-------------------	---------------------------------

## Chassis

Unit	2U
Dimensions	87 mm (H), 438 mm (W), 770 mm (D),
Drives (optional)	External USB-drives

## Power supply

Power supply unit	2HE Thomas-Krenn Server-Barebone (24x SFF, 24x NVMe)
energy efficiency	96.23%

## environment-requirements

Recommended deployment location	To ensure the optimal cooling of the system, we recommend running the server in an air conditioned server room and as part of a rack installation. The server is not ideal for use in an office environment due to its high noise levels.
---------------------------------	---