


Datasheet

Server cabinet Vertiv Knürr 9U / 15U / 24U

[Ver. 1.0]

Highlights at a glance:

- Height 9/15/24U - width 600 - depth 900 mm
- 4 adjustable feet
- Fulfills protection IP20
- Load capacity 2000N (static)
- With front and rear perforated doors for optimal airflow
- Removable covers accessible from all sides
- TÜV-quality test
- Supplied in elegant black, RAL 7021
- Door opening angle 180°
- With special 19" server profiles for mounting trade standard servers



Dimensions

Unit	9U
Height	9U: 478mm; 15U: 745mm; 24U 1145mm
Width	600 mm (W)
Depth	900 mm (D)
Weight	9HE:21kg / 15HE: 29kg / 24HE: 41kg

specifications

specifications	• Installation of rack rails and 19'-intermediate floors possible • fixed 19'-fitting front and back • universal access, depth of casing removed • for improvements in accordance with IEC 297-3 • Optional cable entry via plinth and cover • Rear cable entry completely disassembled • Derivation of lost heat through lifted fan roof • Door-opening-angle 180° for mounting of 19'-components front and rear • Devices with maximum width of 450mm • Installation Accessories
Shunting space	frontsided 75 mm
capacity	2000 N (0.2 T) static
degree of protection	IP20
Tests	• Earthing according to VDE 0701-1 • Vibration Resistant according to MIL-STD 810 E • IP test according to DIN EN 60529

material / surface

Base frame	Aluminum extrusion profile, bare
Corner bracket	aluminium diecast, blank
cover panel component	Stal plate galvanized, powder-coated structure
doors	steel panel, powder coated structure
Multifunction slats	steel panel, galvanized
Color	Visible surfaces of the fairing parts RAL 7021 dark-gray

Scope of supply / Delivery condition

Scope of delivery	1x Base 2x side panels, closed, hinged on both sides 1x cap, closed 1x Front door with perforation, lockable 1x rear-door with perforation, lockable 4x 19' Server steel breadboarded profiles 1x earthing set 4x Levelingfeet
Delivery condition	mounted

optional accessories

Attachments	• Knürr lid/bottom with cable entry • Knürr Socket • Knürr base panel with cable entry • Steering roller kit
Cable management	• Knürr brushes insert for server cabinet • Knürr velcro straps • Knürr marshalling iron • Knürr jumper bracket
Accessories	• Knürr ausziehbarer Gerätefachboden (Vollauszug inkl. Montagematerial) • Knürr Miracel HE-Maßband
Network Accessories	• Kabeldurchführungspanel (5 x Bügel) • RMS Web thermometer
Multiple socket outlets	• 6fach Steckleiste m. Überspannungsschutz/Filter • Power strip 8fold IP 19